

### Listing of Claims:

This listing of claims reflects all claim amendments and replaces all prior versions, and listings, of claims in the application. Material to be inserted is in underline, and material to be deleted is in ~~strikeout~~ or (if the deletion is of five or fewer consecutive characters or would be difficult to see) in double brackets [[ ]]. Any cancellations are without prejudice.

1. (Currently Amended) An exhaust pipe collecting structure for a multi-cylinder engine unit having multiple cylinders, in which exhaust pipes extend from at least four cylinders of the multiple cylinders and are collected into one exhaust passage at a location downstream in a flow of exhaust gases, the structure comprising:

a first exhaust pipe group and a second exhaust pipe group each of which is comprised of two exhaust pipes selected from four exhaust pipes respectively connected to the four cylinders at upstream end portions thereof;

a first exhaust sub-collecting pipe ~~east integrally with the first exhaust pipe group and~~ configured to collect the first exhaust pipe group to form one exhaust passage;

a second exhaust sub-collecting pipe ~~east integrally with the second exhaust pipe group and~~ configured to collect the second exhaust pipe group to form another exhaust passage;

a first joint portion ~~east integrally~~ formed at a downstream end portion of the first exhaust sub-collecting pipe, the first joint portion including a first semi-cylindrical peripheral wall having a joint face defining the opening and extending along a direction of the flow of the exhaust gases; and

a second joint portion ~~east integrally~~ formed at a downstream end portion of the second exhaust sub-collecting pipe, the second joint portion including a second semi-cylindrical

peripheral wall having an opening with a joint face defining the opening and extending along a direction of flow of the exhaust gases; and wherein

a fastener device;

wherein the first exhaust sub-collecting pipe includes the first exhaust pipe group and the first joint portion and is formed in one unitary, integrally cast piece, and the second exhaust sub-collecting pipe includes the second exhaust pipe group and the second joint portion and is formed in one unitary, integrally cast piece, each of the unitary, integrally cast pieces being separable from the other;

and wherein the opening of the first joint portion is opened toward the second joint portion and the opening of the second joint portion is opened toward the first joint portion, the first joint portion and the second joint portion are separably joined to each other at the joint faces thereof by ~~[[a]]~~the fastening device to form the one exhaust passage including the first semi-cylindrical peripheral wall and the second semi-cylindrical peripheral walls~~such that the exhaust passage of the first exhaust sub-collecting pipe and the exhaust passage of the second exhaust sub-collecting pipe are collected together into a common exhaust passage at the first and second joint portions.~~

2. (Cancelled)

3. (Currently Amended) The exhaust pipe collecting structure according to Claim ~~[[2]]~~1, further comprising a rubber tube that covers an outer periphery of the first and second semicylindrical peripheral walls that are joined to face each other.

4. (Currently Amended) An exhaust pipe collecting structure for a multi-cylinder engine unit having multiple cylinders, in which exhaust pipes extend from at least four cylinders of the multiple cylinders and are collected into one exhaust passage at a location downstream of the exhaust pipes in a flow of exhaust gases, the structure comprising:

a first exhaust pipe group and a second exhaust pipe group each of which is comprised of two exhaust pipes selected from four exhaust pipes respectively connected to the four cylinders at upstream end portions thereof;

a first exhaust sub-collecting pipe ~~east integrally with the first exhaust pipe group, and~~ configured to collect two exhaust pipes of the first exhaust pipe group to ~~integrally~~ form one exhaust passage;

a second exhaust sub-collecting pipe ~~east integrally with the second exhaust pipe group, and~~ configured to collect two exhaust pipes of the second exhaust pipe group to ~~integrally~~ form another exhaust passage;

a first joint portion ~~east integrally~~ **formed** at a downstream end portion of the first exhaust sub-collecting pipe;

a second joint portion ~~east integrally~~ **formed** at a downstream end portion of the second exhaust sub-collecting pipe, the second joint portion being arranged in parallel with the first joint portion; and

**wherein the first exhaust sub-collecting pipe includes the first exhaust pipe group and the first joint portion, and is formed in one unitary, integrally cast piece, and the second exhaust sub-collecting pipe includes the second exhaust pipe group and the second joint portion, and is formed in one unitary, integrally cast piece, the unitary, integrally cast pieces being separable from each other;**

**the exhaust pipe collecting structure further comprising:**

a connecting tube located downstream of the first and second joint portions, for allowing the exhaust gases flowing through the exhaust passages inside the first and second joint portion to be led into a common exhaust passage[[;]], **the connecting tube being separable from the unitary, integrally cast piece of the first exhaust sub-collecting pipe and the unitary, integrally cast piece of the second exhaust sub-collecting pipe;**

**wherein the connecting tube includes two parts having a joint surface at which the two parts are jointed to each other, the joint surface extending along a longitudinal direction of the connecting tube.**

~~wherein the first joint portion, the second joint portion, and the connecting tube are separably joined by a fastening device.~~

5. (Canceled)

6. (Cancelled)

7. (Currently Amended) The exhaust pipe collecting structure according to Claim [[6]]4, wherein the first and second exhaust sub-collecting pipes and the connecting tube have double-walled structures to have cooling passages between walls.

8. (Previously Presented) An exhaust pipe collecting structure for a multi-cylinder engine unit having multiple cylinders, in which exhaust pipes extend from at least four cylinders of the multiple cylinders and are collected into one exhaust passage at a location downstream in a

flow of exhaust gases, the structure comprising:

an exhaust manifold having an upstream end portion which is connected to the cylinders and including a plurality of exhaust passages corresponding to exhaust ports of the cylinders, respectively;

a connecting tube connected to a downstream end of the exhaust manifold, the connecting tube including a plurality of connecting exhaust passages communicating with the plurality of exhaust passages of the exhaust manifold and being merged into the one exhaust passage at a location inside the connecting tube;

wherein at least a downstream end portion of the exhaust manifold includes the exhaust passages which are arranged in two lines and forms an integral tube; and

wherein a casting parting plane of the exhaust manifold is provided between the two lines of the exhaust passages.

9. (Previously Presented) The exhaust pipe collecting structure according to Claim 8, wherein the multiple cylinders are four cylinders.

10. (Previously Presented) The exhaust pipe collecting structure according to Claim 9, wherein the exhaust manifold is integrally cast by locating the casting parting plane of the exhaust manifold within one continuous plane.

11. (Previously Presented) The exhaust pipe collecting structure according to Claim 9, wherein the exhaust manifold includes a first water jacket formed therein so as to substantially

define two groups of the exhaust passage of the exhaust manifold at a connecting portion between the exhaust manifold and the connecting tube; and

wherein the connecting tube includes:

a second water jacket extending from the connecting portion between the exhaust manifold and the connecting tube to a position upstream of the single one exhaust passage so as to substantially define two groups of the connecting exhaust passages.

12. (Canceled)

13. (Previously Presented) The exhaust pipe collecting structure according to Claim 11, wherein the second water jacket of the connecting tube is configured to cross the first water jacket of the exhaust manifold at center portions in cross-sections of the exhaust manifold and the connecting tube.

14. (Previously Presented) The exhaust pipe collecting structure according to Claim 13, wherein the second water jacket and the first water jacket respectively have increased water flow sections at the center portion.